

Apparel Systems

Paxar SNAP™ 500 - Care Label Printer

Produce care labels when and where you need them. This breakthrough printer is easy to operate and maintain, remarkably reliable, and surprisingly affordable. Dramatic new styling. Turn it on and discover innovative features like remote diagnostics and software upgrades via the internet, and voice prompts. You can set it up yourself and be up and running quickly. Want the flexibility of printing your own care labels? The Paxar SNAP 500 printer will surpass your expectations and save you time and money.

Features

Design and print two-sided brand/care labels

One-color front and back, 1/1.

2 in/ 51 mm wide print area

Use rolled graphics supplies for more colorful logos, pre-printed non-variable information.

High resolution - 300 dots per inch/ 11.8 dots per mm

Fast - prints up to 7 inches/ 178 mm per second (dependent upon supplies).

Cuts and stacks

Cost effective at any volume

Easily handles millions of labels per year

Voice Prompts - communicates status and error messages in multiple languages (operator selectable).

Count on Paxar to make in-plant printing a SNAP.

Modules

Rotary Knife Module - Simple and durable. Included in the base printer.

Sonic Knife Module - Compact and robust. High-powered sonic module cuts and seals the ends of satin tape labels. Check with Marketing on availability.

Down Stacker Assembly - Simple. Inexpensive. Included with the base printer or with the sonic knife module.

Supplies

Coated, satin weave, or woven edge care label tapes

• Heat seal tapes

• Thermal transfer ink ribbons



Paxar SNAP 500 Printer

- Two-side printer
- Prints care labels
- Includes down stacker and PCMate Platinum label design and printing software.

Ask about ways to manage your investment:

- Consignment and package plans where the printer price is applied to supply purchases
- Rental Agreements

Paxar Technical Service

- Extend the life of your investment by adding a maintenance agreement to your printer
- Save money over time by keeping your printer running longer
- Telephone, depot or onsite options

Paxar Supplies

- Use Paxar thermal transfer tapes and inks for longer machine life
- Paxar supplies are specially designed to work with Paxar printers and software to produce the finest print quality
- If you have any problems, we handle it all

PC Hardware Minimum Requirements

- IBM compatible personal computer
- Windows® 2000, XP
- 128 MB RAM
- 1 GB available disk space
- Pentium® III processor (400 MHz)
- Monitor screen resolution 1024x768
- CD ROM
- Null modem serial cable with DB9F connector
- May need USB/serial adapter.

SpecStar

- Optional label data management products.
- Update printer software, control label data, troubleshoot from anywhere via the internet.

Detailed Features

Tape Arbor

Tape roll slides on, centers, and secures easily - *faster loading and unloading.*

Tape roll size - max 11.5 in/ 292 mm OD. Handles larger supply rolls than most printers – *more throughput, the printer is down less often to reload stock.*

Ink Arbors

Ink rolls slide on. Self-centering mechanism aligns ink ribbon with tape - *easy threading.*

Print Stations

Print heads are easy to clean and quick to replace - *easy maintenance.*
Squareness and tangent (position of the head over the platen roller) are factory set to a fixed position - *no adjustments.*
Adjust contrast with the turn of the knob - while printing.

Top Reflective Sensor - Check with Marketing on availability.

Reads sense mark printed on front of preprinted tape, centered in web - *no adjustments.*

Rotary Knife Assembly

Knife is durable. Loosen a single screw to replace the assembly - *no special tools.*

Simple and Intuitive

Printer Control Panel - Start or stop printing, view status and error indicators, select voice prompts.
Virtual Control/Display - Use PCMate Platinum to set printer adjustments and retrieve status information from your PC monitor - *more accuracy, fewer errors.*

PC Remote Diagnostics

Use PCMate Platinum and SpecStar to update software, control label printing data, troubleshoot from anywhere via the internet - *versatile.*

Graphics and Text

- True Type Fonts
- Point size - 4 point - 96 point (dependent upon supplies)
- Logo and Field rotations - 0, 90, 180, and 270°
- Care Symbols - ASTM, Ginetex
- Justification - Left, right, center, field selectable

Paxar SNAP 500 Printer, Made in USA, US Patents pending
©2005 Paxar Corporation, Inc. All rights reserved. Printed in USA.

Options

Remote Control/Display Module

Back reflective sensor – Reads black sense mark printed on back of white preprinted tape, centered.

Contrast sensor – Reads sense mark printed on front of preprinted tape, centered in web. Sense mark or tape may be colored.

Specifications

Label Size

- Minimum web - 0.5 in/ 25.4 mm
- Minimum pull, using rotary knife
 - 1.0 in/ 25.4 mm - up to 6 ips
 - 1.2 in/ 30.5 mm - 7 ips
- Minimum pull, using sonic knife module option
 - 1.2 in/ 30.5 mm - 3 ips
 - 1.8 in/ 45.8 mm - 4.5 ips
 - 2.4 in/ 61 mm - 6 ips
 - 2.8 in/ 71.2 mm - 7 ips
- Stacking
 - Max. 2.25 in x 5 in/ 57 x 127 mm with standard down stacker
 - Max. pull - 8 in/ 203 mm with optional extension tray
- Max web to pull ration is 1:5

Print Area

•2.0 in x 13.875 in/51 mm x 35 cm- no cut

Print Head Resolution – 300 dpi/ 11.8 dots per mm

Print Speeds

•3 - 7 inches per sec / 76 - 178 mm per sec

Reflective Sensors - Black preprinted sense mark, minimum size 0.375 in x 0.125 in /10 mm x 3.2 mm with a minimum 0.375 in/10 mm white clearance prior to the sense mark.

Barcodes - UPCA, UPCE, Code 39, Code 128, Code 128EDI, Code 93, EAN8, EAN13, Interleaved 2 of 5, Sears Code 39, Datamatrix

Interface

- Paxar PCL (requires null modem serial cable with DB9F connector)
- USB (requires USB/Serial adapter)

Electrical - 90-132/180-265 VAC (switch selectable)
50-60Hz 10 Amp

Weight

Printer - 45 lb./ 20.5 kg
In Shipping Carton - 65 lb./ 30 kg

Mounting - Bench top

Temperature - 41°F/ 5°C to 104°F/ 40°C

Humidity - 5% to 90% non-condensing

FOR MORE INFORMATION CONTACT:

Paxar Corporation
Apparel Systems
1 Wilcox Street
Sayre, PA 18840

U.S. Phone: 1.866.500.SNAP (7627)
Email: snap@paxar.com
www.snapprinter.com

Specifications subject to change without notice.
AS-PS-0081 (June 20, 2005)
Rev. 4